

# Delock Converter SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) with USB Type-C™ male > 22 pin SATA 6 Gbps male incl. power supply

#### Description

This Delock converter can be connected via USB Type-C™ interface to a PC or laptop. Thus, different SATA devices with 22 pin SATA interface can be operated. The included power supply can be used for 3.5" SATA HDDs or optical drives.



#### Item no. 62715

EAN: 4043619627158 Country of origin: China Package: Retail Box

#### **Specification**

- Connector:
  - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type-CTM male >
  - 1 x SATA 6 Gb/s 22 pin male
  - 1 x DC jack
- Chipset: Asmedia ASM1351
- For SATA HDD, SATA SSD, optical drive etc.
- Supports SATA 1.5 Gb/s, SATA 3 Gb/s and SATA 6 Gb/s
- Data transfer rate up to:
  - SuperSpeed USB 10 Gbps,
  - SuperSpeed USB 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
  - SATA 6 Gbps
- LED indicator
- Bootable
- Plug & Play





• Length incl. connector: ca. 24.5 cm

## Power supply specification

· Wall power supply

• Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A

• Output: 12 V / 1.8 A

• Ground outside, plus inside

• Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9.5 mm

#### System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac OS 10.12
- PC or laptop with a free USB Type-C™ port

## **Package content**

- Converter USB Type-CTM SATA 6 Gb/s
- · External power supply
- User manual

#### **Images**











#### General

Function:	Plug & Play bootable
Supported operating system:	Linux Kernel 3.19 or above Mac OS 10.11 or above Windows 10 32-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit
LED indicator:	Activity

# Interface

Connector 1:	1 x USB 10 Gbps USB Type-C™ male
Connector 2:	1 x SATA 6 Gb/s 22 pin plug
connector 3:	1 x DC jack

## **Technical characteristics**

Data transfer rate:	6 Gb/s

# **Physical characteristics**

Cable length:	15 cm
Colour:	black

# **Power supply**

Type:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.5 A
Output:	12 V / 1.8 A
Connector:	DC male 5.5 mm x 2.1 mm





Cable length: 1.75 m

