

Delock Digital Audio Converter Coaxial > TOSLINK

Description

The Delock audio converter converts a coaxial S/PDIF audio signal into an optical S/PDIF signal. A device with a coaxial digital output can be connected to a device with a TOSLINK input.



Specification

- Connector:
 - Input:
 - 1 x Coaxial female S/PDIF
 - 1 x USB Type Micro-B female (5 V power supply)
 - 1 x DC 3.5 x 1.35 mm female (5 V power supply)
 - Output:
 - 1 x TOSLINK female S/PDIF
- Supported sample rates: 44.1 / 48 / 96 / 192 kHz
- Supports Dolby Digital and DTS 5.1 Audio
- Robust metal housing
- Dimensions (LxWxH): ca. 63 x 53 x 23 mm

System requirements

- A free S/PDIF female port
- Connection cables
- A free USB Type-A female port

Package content

- Converter Coaxial > TOSLINK
- USB Type-A to Type Micro-B cable, length ca. 1 m

Item no. 62790

EAN: 4043619627905

Country of origin: China

Package: Box

Images



General

Specification: DTS Audio
Dolby Digital
LPCM

Interface

Output: 1 x TOSLINK female
Input: 1 x Coaxial female S/PDIF
1 x 5 V DC female 3,5 mm x 1,35 mm
1 x USB 2.0 type Micro-B female

Physical characteristics

Housing colour: black
Housing material: metal
Length: 63 mm
Width: 53 mm
Height: 23 mm