

Delock External USB 3.2 Gen 1 Hub USB Type-A > 3 x USB Type-A + 2 Slot SD Card Reader

Description

This USB Hub by Delock can be connected to a computer via the USB Type-A interface. It expands the computer by three USB Type-A connectors as well as two slots for SD and Micro SD memory cards. If the hub is connected to a computer with a USB 3.2 interface, a maximum current of 900 mA is divided between the USB ports and the card reader. If necessary, an optional power supply or an optional power cable can be connected to the power socket.



Item no. 62899

EAN: 4043619628995

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A male >
 - 3 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
 - 1 x SD slot
 - 1 x Micro SD slot
 - 1 x 5 V DC jack
- Chipset: Genesys Logic GL3520 (Hub), GL3224 (Card Reader)
- Data transfer rate up to:
 - SuperSpeed USB 5 Gbps,
 - Hi-Speed 480 Mbps,
 - Full-Speed 12 Mbps,
 - Low-Speed 1.5 Mbps
- The Card Reader supports following memory cards:
 - 1. Slot Secure Digital**
SD, SD3.0 UHS-I, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0
 - 2. Slot Micro Secure Digital**
Micro SD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro
- USB cable directly on the hub (length ca. 15 cm)

- Dimensions (LxWxH): ca. 90 x 40 x 13 mm
- 1 x ferrite core
- Colour: black
- Plug & Play

Specification of power connector

- 5 V, ground outside, plus inside
- Dimensions:
 - inside: \varnothing ca. 1.35 mm
 - outside: \varnothing ca. 3.5 mm
 - length: ca. 9 mm
- Optionales Stromkabel: [Delock 82377](#)
- Optionales Netzteil: [Navilock 41337](#)

System requirements

- Android 6.0 or above
- Linux Kernel 2.6.x or above
- Mac OS 10.9 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC or laptop with a free USB Type-A port

Package content

- USB hub + card reader
- User manual

Images



General

Function:	Plug & Play
Supported operating system:	Android 6.0 or above Linux Kernel 2.6 or above Mac OS 10.9 or above Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 11

Interface

Output:	3 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female 1 x SD slot 1 x Micro SD slot 1 x 5 V DC jack
Input:	1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A male

Technical characteristics

Chipset:	Genesys Logic GL3520 GL3224
Data transfer rate:	USB 3.1 Gen 1 up to 5 Gb/s

Physical characteristics

Ferrite core:	1 x
Cable length:	15 cm
Connector finishing:	gold-plated
Length:	90 mm
Width:	40 mm
Height:	13 mm

Colour:

black

