

## Delock Adaptor USB 2.0 Tip-A tată > 4 x Serial RS-232 DB9 tată

### Descriere scurta

Adaptorul USB 2.0 de la Delock vă permite să conectați 4 dispozitive seriale la un port USB liber al calculatorului sau al laptopului.



1,40 m

### Specification

- Conectori:  
1 x USB 2.0 Tip-A, tată >  
4 x RS-232 seriale DB9, tată
- Chipset: FTDI FT4232H
- Rată de transfer a datelor de până la 115,2 Kb/s
- Acceptă: UHCI / OHCI / EHCI
- Conector serial cu șurub
- Acceptă avertizarea de la distanță și gestionarea alimentării
- Lungime cablu: cca 1,4 m

### Cerinte de sistem

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 2.6.x, Mac ex OS 10.9
- PC sau laptop cu un port USB Tip-A liber

### Pachetul contine

- USB 2.0 la 4 x seriale adaptoare
- CD cu drivere
- Manual de utilizare

Nr. 62947


EAN: 4043619629473

Țara de origine: CHINA

Pachet: • Retail Box



### Imagini



General	
Function:	Plug & Play Remote Wake-Up
Specification:	RS-232 (EIA / TIA) USB 2.0
Supported operating system:	Mac OS 10.9 sau superior Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 2.6 sau superior
Indicator cu LED:	Power
Interface	
Conector 1:	1 x USB 2.0 Type-A male
Conector 2:	1 x Serial RS-232 DB9 plug
Technical characteristics	
Chipset:	FTDI FT4232H
Data transfer rate:	4 x up to 115,2 Kbps
FIFO:	4 x 2 KByte
Data transmission:	asynchronous full duplex
Current consumption:	up to 130 mA
Physical characteristics	
Connector color:	roșu galben verde violet
Material carcasă:	Plastic
Cable type:	USB AWM Style 2725 VW-1
Cable colour:	black
Cable length incl. connector:	1,4 m
Pin finishing:	gold-plated
Conductor gauge:	28 AWG data line 24 AWG power line
Tipul șurubului:	#4-40 UNC
Shielding:	double