



## General

Function:	Hot Plug
Specification:	RS-232 (EIA / TIA) Ethernet
Supported operating system:	Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows Server 2012 R2 Windows Server 2016
LED indicator:	power and activity
Protection:	ESD (Electrostatic Discharge)

## Interface

Connector 1:	1 x serial RS-232 DB9 male
Connector 2:	1 x RJ45 jack

## Technical characteristics

Data transfer rate:	up to 115,2 Kb/s Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps
FIFO:	1 kByte
Operating temperature:	0 °C ~ 60 °C
Humidity:	5 ~ 95 %
Data transmission:	asynchronous full duplex
Voltage:	5 V
Current consumption:	500 mA

UART:

Ethernet-UART

### Physical characteristics

Housing colour:	black
Housing material:	Polycarbonat
Weight:	67 g
Cable length:	31 cm
Length:	480 mm
Width:	34 mm
Height:	18 mm

### Power supply

Connector:	DC male 3.5 mm x 1.35 mm
------------	--------------------------