

Delock Adaptor USB 2.0 Tip-A > 2 x interfață serială DB9 RS-232

Descriere scurta

Acest adaptor USB Tip-A la serial de la Delock oferă două interfețe DB9 RS-232 pentru imprimante, instrumente de măsură, controale, dispozitive IoT etc.



1,5 m

Specification

- Conectori:
1 x USB 2.0 Tip-A, tată >
2 x RS-232 seriale DB9, tată
- Chipset: FTDI FT232
- Rată de transfer a datelor de până la 921,6 Kbps
- Acceptă: UHCI / OHCI / EHCI
- Conector serial cu șurub
- Acceptă avertizarea de la distanță și gestionarea alimentării
- Lungime cablu, inclusiv conectori: cca 1,5 m

Nr. 63466

EAN: 4043619634668

Țara de origine: China

Pachet: Retail Box



Cerinte de sistem

- Windows 7/7-64/8.1/8.1-64/10/10-64/11, Linux ex Kernel 2.6.x, Mac ex OS 10.9
- PC sau laptop cu un port USB Tip-A liber

Pachetul contine

- USB 2.0 la 2 x seriale adaptoare
- CD cu drivere
- Manual de utilizare

Imagini



General	
Function:	Plug & Play Remote Wake-Up
Specification:	RS-232 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 sau superior Mac OS 10.9 sau superior Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-bit Windows 8.1 64-bit
Indicator cu LED:	power and activity
Interface	
Conector 1:	1 x USB 2.0 Type-A male
Conector 2:	2 x Serial RS-232 DB9 male
Technical characteristics	
Chipset:	FTDI FT232RL
Data transfer rate:	1 Mbps
FIFO:	2 x 256 Byte receive 2 x 128 byte transmit
Data transmission:	asynchronous full duplex
Physical characteristics	
Connector color:	galben verde
Material carcasă:	Plastic
Cable type:	USB AWM Style 2725
Cable colour:	black
Cable length incl. connector:	1,5 m
Conductor gauge:	26 AWG data line 24 AWG power line
Tipul șurubului:	#4-40 UNC