

# Delock Adapterski kabel USB 2.0 Tip-A na serijski RS-485 s 3 x otvorena kraja žice 2 m

## Opis

RS-485 adapterski kabel tvrtke Delock podržava prijenos podataka između uređaja s USB 2.0 i uređaja s RS-485 sučeljima. RS-485 priključci adaptera prikladni su za pametna brojlja, PV pretvarače, mjerne uređaje itd.

## Otvoreni krajevi žice

S kositrenim otvorenim krajevima žice, veza se može uspostaviti izravno na RS-485 priključak uređaja.



2 m

### Predmet br. 63509

EAN: 4043619635092

Zemlja podrijetla: China

Pakiranje: Plastična vrećica sa zip zatvaračem

## Tehnički podaci

- Priključak:
  - 1 x USB Tipa-A, muški
  - 1 x serijski RS-485 3 x otvoreni krajevi žice (kositreni)
- Skup čipova: FTDI FT232R
- Kompatibilno s UHCI / OHCI / EHCI upravljačem
- Brzina prijenosa podataka do 921,6 Kbps
- Dodjela pinova: T/R (A+) crvena, T/R (B-) bijela, GND zelena
- Promjer kabela: oko 5 mm
- Provodnik: lančana bakrena žica
- Izolator: PVC
- Duljina kabela zajedno s priključkom: oko 2 m
- Boja: crno

## Preduvjeti sustava

- Linux Kernel 5.19 ili noviji
- Windows 10/10-64/11

- Osobno ili prijenosno računalo sa slobodnim USB Tipa-A priključkom
- 

## Sadržaj pakiranja

- USB Tip-A na RS-485 adapter
- 

## Slike



## General

Funkcija:	Plug & Play
Tehnički podaci:	RS-485 USB 2.0
Supported operating system:	Linux Kernel 2.6 ili noviji Windows 10 32-bit Windows 10 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows Server 2012 R2 Windows Server 2016 Windows Server 2019 Mac OS 11.1 or above Windows 11
Protection:	ESD (Electrostatic Discharge)

## Interface

Priključak 1:	1 x USB Tipa-A muški
Priključak 2:	RS-485 3 x open tinned wire

## Technical characteristics

Skup čipova:	FTDI FT232RL
Brzina prijenosa podataka:	up to 921.6 Kbps
FIFO:	1 x 128 byte receive 1 x 256 byte transmit
Signal transmission:	T/R+, T/R-, GND
Data transmission:	Poludupleks asynchronous Bi-directional differential
UART:	USB to serial UART
Support:	Modbus

## Physical characteristics

Kućište boja:	crne
Cable type:	AWM STYLE 2464 24AWG 80°C 300V VW-1
Boja kabela:	crne
Cable length incl. connector:	2 m
Shielding:	Aluminum foil