

# Delock USB Type-C™ Adapter to 2.5 Gigabit LAN with USB Type-A female

## Description

The adapter by Delock expands a device with USB-C™ or Thunderbolt™ 3 port by one **network interface** and one SuperSpeed **USB Type-A female**.

### NBASE-T for higher speed

Modern services and new technologies require higher bandwidths. NBASE-T technology enables speeds of 1 Gbps and **2.5 Gbps** with conventional networking cables. The best possible transmission rate is set automatically.

### Additional USB Type-A port

A USB memory, mouse or keyboard can be connected to the USB Type-A port.



**Item no. 63826**

EAN: 4043619638260

Country of origin: China

Package: Retail Box

## Specification

- Connectors:
  - 1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ male
  - 1 x Gigabit LAN RJ45 jack
  - 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
- Chipset: Realtek RTL8156, Genesys Logic GL3510
- SuperSpeed USB - 5 Gbps specification
- Data transfer rate:
  - Ethernet up to 10 Mbps (Half/Full Duplex)
  - Fast Ethernet up to 100 Mbps (Half/Full Duplex)
  - Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)
  - NBASE-T with up to 2.5 Gbps (Half/Full Duplex)
- Compatible with:
  - IEEE 802.3: 10BASE-T
  - IEEE 802.3u: 100BASE-TX
  - IEEE 802.3ab: 1000BASE-T
  - IEEE 802.3bz: 2.5GBASE-T
- Supports Auto MDI-X (automatic detection of standard or crossover network cable)
- Supports IEEE 802.3az (Energy Efficient Ethernet)

- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation with back-pressure
- Supports 16k Jumbo Frames
- LED indicator for link and activity
- USB bus powered
- Colour: black
- Dimensions (LxWxH): ca. 82 x 29 x 15 mm
- Cable length without connectors: ca. 15 cm

---

## System requirements

- Chrome OS 83.0 or above
- Linux Kernel 4.6.4 or above
- Mac OS 10.15.6 or above
- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port

---

## Package content

- USB Type-C™ 2.5 Gigabit LAN adapter
- User manual

---

## Images



## General

|                             |   |
|-----------------------------|---|
| Supported operating system: | Chrome OS<br>Linux Kernel 4.6.4 or above<br>Mac OS 10.15.6 or above<br>Windows 10 32-Bit<br>Windows 10 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |
| LED indicator:              | power and activity  |

## Interface

|              |                                 |
|--------------|---------------------------------|
| Connector 1: | 1 x USB 5 Gbps USB Type-C™ male |
| Connector 2: | 1 x Gigabit LAN RJ45 jack       |
| connector 3: | 1 x USB 5 Gbps Type-A female    |

## Technical characteristics

|                     |  |
|---------------------|--|
| Chipset:            | Realtek RTL8156  |
| Data transfer rate: | Ethernet up to 10 Mbps<br>Fast Ethernet up to 100 Mbps<br>Gigabit Ethernet up to 1 Gbps<br>Gigabit Ethernet up to 2.5 Gbps |

## Physical characteristics

|                   |         |
|-------------------|---------|
| Housing material: | Plastic |
| Cable length:     | 15 cm   |
| Length:           | 82 mm   |
| Width:            | 29 mm   |
| Height:           | 15 mm   |
| Colour:           | black   |