

# Delock Adapter USB Type-C™ > 1 x Serial DB9 RS-232

## Description

This USB Type-C™ to serial adapter by Delock provides a compatible RS-232 DB9 interface for printers, measuring instruments, controllers, IoT devices etc.



ca. 25 cm

## Specification

- Connectors:
  - 1 x USB Type-C™ male
  - 1 x serial RS-232 DB9 male
- Chipset: FTDI FT232RL
- Serial connector with nuts
- Data transfer rate up to 460.8 Kbps
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Cable type: UL 444
- Cable length without connectors: ca. 15 cm
- Colour: black

## System requirements

- Linux Kernel 2.6 or above
- Mac OS 10.13 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ or Thunderbolt™ 3 port

## Package content

- USB Type-C™ to 1 x serial adapter
- Driver CD
- User manual

Item no. 63908


EAN: 4043619639083

Country of origin: China

Package: Retail Box



## Images



General	
Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) Thunderbolt™ 3 USB Type-C™
Supported operating system:	Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Mac OS 10.13 or above Linux Kernel 2.6 or above
Interface	
Output:	1 x serial RS-232 DB9 male
Input:	1 x USB Type-C™ male
Technical characteristics	
Chipset:	FTDI FT232RL
Data transfer rate:	up to 460,8 Kbps
FIFO:	1 x 256 byte receiver 1 x 128 byte transmit
Data transmission:	asynchronous full duplex
UART:	USB to serial UART
Physical characteristics	
Cable type:	UL 444
Cable diameter:	4.4 mm
Cable length incl. connector:	25 cm
Pin finishing:	gold-plated
Conductor gauge:	28 AWG data line 24 AWG power line
Screw type:	#4-40 UNC
Shielding:	double
Colour:	black