

# Adapter USB 2.0 Type-A > 1 x Serial DB9 RS-232 110° angled

## Description

This USB Type-A to serial adapter by Delock provides an RS-232 port for meters, POS systems, printers, modems, IoT devices, etc.



**Item no. 63916**

EAN: 4043619639168

Country of origin: China

Package: Retail Box

## Specification

- Connectors:  
1 x USB 2.0 Type-A male >  
1 x serial RS-232 DB9 male
- Chipset: Prolific PL2303 HXD
- Screw type: #4-40 UNC
- Compatible with USB 2.0, and USB 1.1 full speed 12 Mbps
- Data transfer rate up to 460.8 Kbps
- LED indicator
- Signals: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Parity: even, odd, none, mark, space
- Stop bit: 1, 1.5, 2
- Data bit: 5, 6, 7, 8
- Flow control: none, Xon / Xoff, RTS / CTS
- FIFO: 512 Byte buffer bi-directional


## System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, ex Linux Kernel 2.6, ex Mac OS 10.9
- PC or laptop with a free USB Type-A port

## Package content

- USB 2.0 to 1 x serial adapter
- Driver CD
- User manual

## Images



## General

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 1.1 USB 2.0
Supported operating system:	Linux Kernel 3.3 or above Mac OS 10.12 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

## Interface

Connector 1:	1 x USB 2.0 Type-A male
Connector 2:	1 x Serial RS-232 DB9 male

## Technical characteristics

Chipset:	Prolific PL2303HXD
Data transfer rate:	up to 460,8 Kbps
FIFO:	512 Byte
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous full duplex
Voltage:	USB Bus powered (no additional power supply required)

## Physical characteristics

Cable length incl. connector:	1.8 m
Screw type:	#4-40 UNC
Colour:	black