

Delock Adapter USB Type-C™ male > VGA / HDMI / DVI female white

Description

This adapter by Delock is suitable for the connection of a VGA, HDMI or DVI monitor to a computer with USB-CTM interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a ThunderboltTM 3 interface. Only one monitor can be used on the adapter.



13 cm

Item no. 63924

EAN: 4043619639243 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - 1 x USB Type-C™ male >
 - 1 x VGA 15 pin female
 - 1 x HDMI-A 19 pin female
 - 1 x DVI 24+5 female with nuts
- Chipset: VL100, IT6562FN, PS8222B
- High Speed HDMI specification
- DVI-D (Single Link), VGA not wired
- Only 1 monitor usable with the adapter
- Resolution:

HDMI up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware) DVI and VGA up to 1920 x 1080 @ 60 Hz (depending on the system and the connected hardware)

- Power consumption: max. 1.35 W
- Cable length without connectors: ca. 13 cm
- · Colour: white





System requirements

- iPad Pro (2018)
- Linux Kernel 4.6 or above
- Mac OS 10.13.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

• Adapter USB-CTM to VGA / HDMI / DVI

Images









General

Linux Kernel 4.6 or above
Mac OS 10.13.3 or above
Windows 10 32-Bit
Windows 10 64-Bit
Windows 7 32-Bit
Windows 7 64-Bit
Windows 8.1 32-Bit
Windows 8.1 64-Bit
iPad Pro (2018)

Interface

Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x HDMI-A female
connector 3:	1 x DVI 24+1 female with nuts
connector 4:	1 x VGA 15 pin female

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 30 Hz 1920 x 1080 @ 60 Hz
Maximum power consumption:	1.35 W

Physical characteristics

Ferrite core:	1 x
Colour:	white