

Delock USB Type-C[™] Adapter to mini DisplayPort (DP Alt Mode) 4K 60 Hz - Key Chain

Description

This adapter by Delock is suitable for the connection of a DisplayPort monitor to a computer with USB-CTM interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a ThunderboltTM 3 interface. Due to the small dimensions, the adapter is ideal as on the go companion.



Item no. 63939

EAN: 4043619639397 Country of origin: China Package: Retail Box

Specification

- Connectors:
 1 x USB Type-C[™] male >
 - 1 x mini DisplayPort 20 pin female
- Chipset: VIA VL100
- DisplayPort 1.2 specification
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- USB bus powered
- Plug & Play
- Cable length without connectors: ca. 3 cm
- Colour: black

System requirements

- Android 6.0 or above
- Chrome OS

DATASHEET



- iPad Pro (2018)
- Linux Kernel 4.3.3 or above
- Mac OS 10.13.3 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Windows 10 Mobile
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt[™] 3 port

Package content

• USB-C™ to mini DisplayPort adapter

Images







General

| Function: | Plug & Play |
|-----------|---|
| | Android 6.0 or above Chrome OS Linux Kernel 4.3.3 or above Mac OS 10.13.3 or above Windows 10 32-Bit Windows 10 64-Bit Windows 10 Mobile Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018) |

Interface

| Output: | 1 x mini DisplayPort 20 pin female |
|---------|------------------------------------|
| Input: | 1 x USB Type-C™ male |

Technical characteristics

| Chipset: | VIA VL100 |
|----------------------------|---------------------|
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz |
| Signal transmission: | video audio |

Physical characteristics

Colour: black