

# Delock USB 2.0 na 2 x serijski RS-232 adapter

## Opis

Ovaj prilagodnik EASY-USB Tip-A na serijski tvrtke Delock pruža dva sučelja RS-232 DB9 za pisane, mjerne instrumente, upravljače, IoT uređaje, itd.



0,6 m

### Predmet br. 63950

EAN: 4043619639502

Zemlja podrijetla: China

Pakiranje: Retail Box

## Tehnički podaci

- Priključak:
  - 1 x EASY-USB 2.0 Tipa-A muški >
  - 2 x serijska muška priključka RS-232 DB9 s maticama za vijke
- Skup čipova: ASIX MCS7820
- Podatkovnih bitova: 5, 6, 7, 8
- Stop bitova: 1, 2
- FIFO: 512 bajtni međuspremnik dvosmjerni
- Paritet parni, neparni, nijedan, oznaka, prazno mjesto
- Kontrola protoka: nema, hardver RTS / CTS, softver XON / XOFF
- Signali: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Brzina prijenosa podataka do 460,8 Kb/s
- Podržava: UHCI / OHCI / EHCI
- Serijski priključci s maticama za vijke
- Podržava daljinsko upravljanje aktiviranjem i napajanjem
- Kompatibilno s 16C450 / 16C550 UART
- 1 x feritna jezgra
- Duljina zajedno s priključkom (L): oko 0,6 m




## Preduvjeti sustava

- Linux Kernel 2.6 ili noviji
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Osobno ili prijenosno računalo sa slobodnim USB Tipa-A priključkom

## Sadržaj pakiranja

- EASY-USB 2.0 na 2 x serijski
- CD s upravljačkim programom
- Korisnički priručnik

## Slike



## General

Tehnički podaci:	RS-232 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 ili noviji Windows 10 32-bit Windows 10 64-bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

## Interface

Priključak 1:	1 x Easy USB Type-A
Priključak 2:	2 x serijska muška RS-232 DB9

## Technical characteristics

Skup čipova:	ASIX MCS7820
Brzina prijenosa podataka:	2 x 460.8 Kbps
FIFO:	512 byte
Data transmission:	asynchronous full duplex

## Physical characteristics

Connector color:	crne
Materijal kućišta:	Plastika
Boja kabela:	crne
Cable length incl. connector:	ca. 60 cm
Vrsta vijka:	#4-40 UNC