

# Delock USB 2.0 na 2 x serijski RS-232 adapter

## Opis

Ovaj prilagodnik EASY-USB Tip-A na serijski tvrtke Delock pruža dva sučelja RS-232 DB9 za pisane, mjerne instrumente, upravljače, IoT uređaje, itd.



0,6 m

### Predmet br. 63950

EAN: 4043619639502

Zemlja podrijetla: China

Pakiranje: Retail Box

## Tehnički podaci

- Priključak:
  - 1 x EASY-USB 2.0 Tipa-A muški >
  - 2 x serijska muška priključka RS-232 DB9 s maticama za vijke
- Skup čipova: ASIX MCS7820
- Podatkovnih bitova: 5, 6, 7, 8
- Stop bitova: 1, 2
- FIFO: 512 bajtni međuspremnik dvosmjerni
- Paritet parni, neparni, nijedan, oznaka, prazno mjesto
- Kontrola protoka: nema, hardver RTS / CTS, softver XON / XOFF
- Signali: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Brzina prijenosa podataka do 460,8 Kb/s
- Podržava: UHCI / OHCI / EHCI
- Serijski priključci s maticama za vijke
- Podržava daljinsko upravljanje aktiviranjem i napajanjem
- Kompatibilno s 16C450 / 16C550 UART
- 1 x feritna jezgra
- Duljina zajedno s priključkom (L): oko 0,6 m




## Preduvjeti sustava

- Linux Kernel 2.6 ili noviji
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Osobno ili prijenosno računalo sa slobodnim USB Tipa-A priključkom

## Sadržaj pakiranja

- EASY-USB 2.0 na 2 x serijski
- CD s upravljačkim programom
- Korisnički priručnik

## Slike



## General

|                             |   |
|-----------------------------|---|
| Tehnički podaci:            | RS-232 (EIA / TIA)<br>USB 2.0   |
| Supported operating system: | Linux Kernel 2.6 ili noviji<br>Windows 10 32-bit<br>Windows 10 64-bit<br>Windows 7 32-Bit<br>Windows 7 64-Bit<br>Windows 8.1 32-Bit<br>Windows 8.1 64-Bit |

## Interface

|               |                               |
|---------------|-------------------------------|
| Priključak 1: | 1 x Easy USB Type-A           |
| Priključak 2: | 2 x serijska muška RS-232 DB9 |

## Technical characteristics

|                            |                             |
|----------------------------|-----------------------------|
| Skup čipova:               | ASIX MCS7820                |
| Brzina prijenosa podataka: | 2 x 460.8 Kbps              |
| FIFO:                      | 512 byte                    |
| Data transmission:         | asynchronous<br>full duplex |

## Physical characteristics

|                               |           |
|-------------------------------|-----------|
| Connector color:              | crne      |
| Materijal kućišta:            | Plastika  |
| Boja kabela:                  | crne      |
| Cable length incl. connector: | ca. 60 cm |
| Vrsta vijka:                  | #4-40 UNC |