

Delock USB Charger 1 x USB Type-C™ PD + 3 x USB Type-A 60 W + 12 W

Description

This USB Power Delivery (PD) charger by Delock can be used to charge laptops with USB Type-C™ connector. It provides various voltages from 5 V to 20 V and power up to 60 Watt. In addition, 3 USB Type-A 5 V connectors with intelligent charging technology are available for conventional devices.



Specification

- Connectors:
 - 1 x USB Type-C™ female
 - 3 x USB Type-A female
 - 1 x IEC-60320-C8 connector
- Input:
 - AC 100 ~ 240 V / 50 ~ 60 Hz / 1.5 A
- Output:
 - USB Type-C™ 5.0 V / 9.0 V / 12.0 V / 15.0 V / 20.0 V 3.0 A (max. 60.0 W)
 - USB Type-A 5.0 V / 2.4 A (max. 12.0 W)
- Output power: max. 72.0 W total
- Average active efficiency 84.49 % (5.0 V / 3.0 A + 5.0 V / 2.4 A)
- Average active efficiency 88.57 % (20.0 V / 3.0 A + 5.0 V / 2.4 A)
- Efficiency at low load (10 %) 78.99 % (5.0 V / 3.0 A + 5.0 V / 2.4 A)
- Efficiency at low load (10 %) 80.53 % (20.0 V / 3.0 A + 5.0 V / 2.4 A)
- No-load power consumption 0.187 W
- USB Power Delivery (PD) 3.0
- Overload protection
- Over current protection
- Overheating protection
- Short circuit protection
- Operating temperature: 0 °C ~ 40 °C
- Storage temperature: -20 °C ~ 80 °C
- Colour: black
- Dimensions (LxWxH): ca. 91.0 x 75.0 x 27.5 mm

System requirements

- Device with a free USB port
- Connection cables

Package content

- USB charging station
- Power cord, length ca. 1.2 m
- User manual

Item no. 63974

EAN: 4043619639748

Country of origin: China

Package: • Retail Box

Images



Physical characteristics

Housing colour: black

Power supply

Type: Power supply with IEC connector

Input: AC 100 - 240 V / 50 - 60 Hz / 1,5 A

Output: 5.0 V / 3.0 A
5 V / 2.4 A
9.0 V / 3.0 A
12.0 V / 3.0 A
15.0 V / 3.0 A
20.0 V / 3.0 AConnector: 1 x USB Type-C™ female
3 x USB Type-A female