

# Delock Front Panel 3.5" USB 5 Gbps 1 x USB Type-C™ + 2 x USB Type-A + SD and Micro SD slot

## Description

This front panel by Delock can be installed into a free 3.5" bay of a computer. It has two USB 5 Gbps Type-A and one USB 5 Gbps Type-C port. It will be connected to the motherboard internally via a pin header male port.



## Integrated Card Reader

In addition, the hub with integrated card reader expands the PC by an SD and a Micro SD slot.

**Item no. 64058**

EAN: 4043619640584

Country of origin: China

Package: Retail Box

## Specification

- Connectors:
  - external:
    - 1 x USB 5 Gbps USB Type-C™ female
    - 2 x USB 5 Gbps Type-A female
    - 1 x SD slot
    - 1 x Micro SD slot
  - internal:
    - 1 x 19 pin USB pin header female port on the cable
    - 1 x SATA 15 pin power connector
- Chipset: VIA VL817, Genesys Logic GL3224
- Data transfer rate up to:
  - SuperSpeed 5 Gbps,
  - Hi-Speed 480 Mbps,
  - Full-Speed 12 Mbps,
  - Low-Speed 1.5 Mbps
- The Card Reader supports following memory cards:
  1. Slot Secure Digital
    - SD, SD3.0 UHS-I, SD High Capacity (SDHC), SD Ultra, SDHC Ultra, SDXC, MMC-I, MMC-II, MMC 4.0, Mini SD, Mini SDHC, MMCmobile, RS-MMC, RS-MMC 4.0

## 2. Slot Micro Secure Digital

MicroSD, Micro SDHC, Micro SDHC Ultra, T-Flash, MMCmicro

- Cable data:  
1 x 19 pin USB pin header female cable, length ca. 54 cm (without connectors)
- 3.5" metal frame
- Colour: black
- Hot Swap, Plug & Play

---

## System requirements

- Linux Kernel 3.3 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free 3.5" bay
- Motherboard with a free 19 pin USB 5 Gbps pin header male
- Power supply with SATA 15 pin receptacle

---

## Package content

- 3.5" front panel
- USB pin header female cable
- Screws
- User manual

---

## Images



## General

Form factor:	3.5"
Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 3.3 or above Windows 10 64-Bit Windows 8.1 64-Bit

## Interface

External:	1 x Micro SD Slot 1 x SD slot 1 x USB 5 Gbps USB Type-C™ female 2 x USB 5 Gbps Type-A female
Internal:	1 x 19 pin USB 5 Gbps pin header female 1 x SATA 15 pin power connector

## Technical characteristics

Data transfer rate:	USB 3.2 Gen 1 up to 5 Gbps
---------------------	----------------------------

## Physical characteristics

Housing material:	metal
Length:	102 mm
Width:	95 mm
Height:	26 mm
Colour:	black