

Delock USB Type-C[™] Adapter to DisplayPort (DP Alt Mode) 8K with HDR and Power Delivery 60 W

Description

This adapter by Delock is suitable for the connection of a DisplayPort monitor in **8K Ultra HD** (7680 x 4320 @ 60 Hz) resolution to a computer with **USB-C™** interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface.



This adapter has a USB Type-CTM Power Delivery port. If this port is connected to the power supply of the laptop or tablet, the host device is charged with up to 60 watts during operation.



Item no. 64202

EAN: 4043619642021 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - 1 x USB Type-C™ male
 - 1 x DisplayPort female
 - 1 x USB Type- C^{TM} PD female (power supply)
- DisplayPort 1.4 specification
- · Resolution:

with DSC:

7680 x 4320 @ 60 Hz

3840 x 2160 @ 144 Hz

without DSC:

7680 x 4320 @ 30 Hz

3840 x 2160 @ 120 Hz

(depending on the system and the connected hardware)

- Transmission of audio and video signals
- Supports 3D displays
- Supports HDR10
- Supports HDCP 1.4 and 2.2
- Output power for host: max. 60 W
- Plug & Play



- · Housing material: aluminium
- Cable length without connectors: ca. 13 cm
- · Colour: black

System requirements

- Android 11.0 or above
- Chrome OS
- Linux Kernel 5.11 or above
- Mac OS 12.2.1 or above
- Windows 8.1/8.1-64/10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-C™ to DisplayPort adapter
- User manual

Images







General

Function:	Plug & Play HDR / HDR10
Supported operating system:	Chrome OS Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Linux Kernel 5.11 or above Mac OS 12.2.1 or above Android 11.0 or above

Interface

Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x DisplayPort female
connector 3:	1 x USB Type-C [™] Power Delivery female

Technical characteristics

|--|