

Delock HDMI Extender Set over Cat.6 cable 4K 30 Hz

Description

This **HDMI extender set** by Delock can transmit high-resolution video / audio signals and an IR control signal over a single **network cable**. At **4K 30 Hz** resolution, distances of **up to 40 m** are possible, and at 1080p resolution, 70 m can be achieved. The set has wide applications in conference rooms, for tele-education or on large screens.



HDMI loop output

The transmitter has an HDMI loop output, so the signal can be **cascaded** to the next extender or to a monitor.

Power over Cable (PoC)

The set supports Power over Cable (PoC), so only the transmitter requires a power supply. The receiver is **powered via the network cable** and can therefore be used more flexible.

Screwable DC connection

The power supply with screwable connector ensures a secure and reliable connection - perfect **for professional installations** to avoid accidental disconnection.

Item no. 65832

EAN: 4043619658329

Country of origin: China

Package: Retail Box

Specification

- Connectors Transmitter:
 - Input:
 - 1 x HDMI-A female
 - 1 x DC 12 V power connector screwable
 - Output:
 - 1 x RJ45 jack
 - 1 x HDMI-A female
 - 1 x 3.5 mm 3 pin stereo jack female (IR)
- Connectors Receiver:
 - Input:
 - 1 x RJ45 jack
 - 1 x 3.5 mm 3 pin stereo jack female (IR)

Output:

1 x HDMI-A female

- Transmission of audio and video signals
- Transmission of IR signals 30 - 60 kHz
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Supports EDID und HDCP
- Supports PoC (Power Over Cable)
- Power consumption: max. 3.0 W
- Metal housing
- Wall-mount option
- Colour: black
- Dimensions (LxWxH): ca. 80 x 69 x 17 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 12.0 V / 1.0 A / 12.0 W
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9 mm

System requirements

- HDMI cable
- One Cat.5e or Cat.6 network cable

Package content

- HDMI transmitter
- HDMI receiver
- Infrared transmitter
- Infrared receiver
- Power supply
- User manual

Images



Transmitter



Receiver



General

| | |
|----------------|---------------|
| Mounting type: | Wall mounting |
|----------------|---------------|

Interface

| | |
|--------------|-------------------------------------|
| Connector 1: | 1 x HDMI-A female |
| Connector 2: | 1 x RJ45 jack |
| connector 3: | 1 x DC jack |
| connector 4: | 1 x 3.5 mm 3 pin stereo jack female |

Technical characteristics

| | |
|----------------------------|---------------------|
| Maximum screen resolution: | 3840 x 2160 @ 30 Hz |
|----------------------------|---------------------|

Physical characteristics

| | |
|-------------------|-------|
| Housing colour: | black |
| Housing material: | metal |