

Delock Mini DisplayPort to HDMI adapter with latch 4K 60 Hz active

Description

This mini DisplayPort adapter by Delock can be used to connect a HDMI monitor to graphics cards with mini DisplayPort ports that have special notches in the slot bracket above the ports. The additional latch of the plug of the adapter snaps into the notch and prevents the adapter from being pulled out unintentionally.



Item no. 65980

EAN: 4043619659807

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x mini DisplayPort male with latch >
 - 1 x HDMI-A female
- Chipset: MegaChips MCDP2900
- DisplayPort 1.4 specification
- High Speed HDMI with Ethernet (HEC) specification
- Active converter, for graphics cards with DP and DP++ output
- Cable gauge: 32 AWG
- Cable diameter: ca. 4.8 mm
- Contacts gold-plated
- LS0H (halogen-free)
- Resolution up to 3840 x 2160 @ 60 Hz
(depending on the system and the connected hardware)
- Transmission of audio and video signals
- Supports 3D displays
- Supports HDR
- Supports HDCP 1.4 and 2.2
- Cable length incl. connectors: ca. 15 cm
- Colour: black

System requirements

- A free mini DisplayPort female port

Package content

- Adapter mini DisplayPort to HDMI

Images



General

Specification:	High Speed HDMI with Ethernet HDCP 1.4 HDCP 2.2 DisplayPort 1.4 HDR
----------------	---

Interface

Connector 1:	1 x mini DisplayPort male
Connector 2:	1 x HDMI-A female

Technical characteristics

Chipset:	MegaChips MCDP2900
Maximum screen resolution:	3840 x 2160 @ 60 Hz

Physical characteristics

Cable length:	15 cm
Pin finishing:	gold-plated
Conductor gauge:	32 AWG
Length:	15 cm
Colour:	black
Cable diameter:	4.8 mm