


# Delock Mini DisplayPort 1.2 to VGA adapter with latch passive

## Description

This mini DisplayPort adapter by Delock can be used to connect a VGA monitor to graphics cards with mini DisplayPort ports that have special notches in the slot bracket above the ports. The additional latch of the plug of the adapter snaps into the notch and prevents the adapter from being pulled out unintentionally.



**Item no. 65981**

EAN: 4043619659814

Country of origin: China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x mini DisplayPort male with latch >
  - 1 x VGA female
- Chipset: Analogix ANX9833
- DisplayPort 1.2 specification
- Passive converter (level shifter), suitable only for graphics cards with DP++ output
- Cable gauge: 32 AWG
- Cable diameter: ca. 4.8 mm
- Contacts gold-plated
- LS0H (halogen-free)
- Resolution up to 1920 x 1200 @ 60 Hz  
(depending on the system and the connected hardware)
- Transfer of digital video signals
- Cable length incl. connectors: ca. 15 cm
- Colour: black

## System requirements

- A free mini DisplayPort DP++ female

---

## Package content

- Adapter mini DisplayPort to VGA

---

## Images



## General

Specification:	DisplayPort 1.2
----------------	-----------------

## Interface

Connector 1:	1 x mini DisplayPort male
Connector 2:	1 x VGA 15 pin female

## Technical characteristics

Chipset:	Analogix ANX9833
Maximum screen resolution:	1920 x 1200 @ 60 Hz

## Physical characteristics

Cable length:	15 cm
Pin finishing:	gold-plated
Conductor gauge:	32 AWG
Colour:	black
Cable diameter:	4.8 mm