


Delock Bloc de conexiuni pentru versiunea cu lipire PCB, îmbinare verticală 3 pini 5,00 mm, 10 bucăți

Descriere scurta

Acest bloc de conexiuni de la Delock este potrivit pentru montarea pe un PCB. Acesta poate fi lipit pe o placă, pentru a crea o conexiune cu șurub. Mai mult, datele sau cablurile de alimentare pot fi conectate prin intermediul blocului de conexiuni.



Nr. 66018

EAN: 4043619660186

Țara de origine: China

Pachet: Pungă din plastic
cu închidere tip fermoar




Specification

- Conectori:
 - 1 x bloc de conexiuni cu șurub, 3 pini
 - 1 x 3 conectori de lipire
- Distanța pas: 5,00 mm
- Temperatura mediului: -40 °C ~ 105 °C
- Utilizabil pentru un cablu de la 24 la 14 AWG
- Rezistența la tensiune: AC 2000 V / 1 min
- Tensiune nominală în funcție de: UL: 300 V, IEC: 250 V
- Curent nominal conform: UL: 10 A, IEC: 24 A
- Rezistența la izolație: 500 MΩ / DC 500 V
- Material: plastic
- Culoare: verde
- Dimensiunii (LxIxÎ): aprox. 17,0 x 15,0 x 12,0 mm

Pachetul contine

- 10 x Bloc de conexiuni

Imagini



General

Suitable for conductor gauge:	24 - 14 AWG
Mounting type:	Soldering

Interface

Conector 1:	1 x bloc de conexiuni cu șurub, 3 pini
Conector 2:	1 x 3 conectori de lipire

Technical characteristics

Storage temperature:	-40 °C ~ 105 °C
Resistor:	500 MΩ / DC 500 V

Physical characteristics

Pitch distance:	5 mm
Material carcasă:	Plastic
Lungime:	17,0 mm
Width:	15,0 mm
Height:	12,0 mm
Colour:	verde