

Delock DIP sliding switch 8-digit 2.54 mm pitch THT vertical blue 10 pieces

Description


This DIP sliding switch by Delock is suitable for the through-hole mounting on a PCB.

THT Assembly Technology

The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

Multifunctional application

The DIP switch is mainly used in telecommunications, computers and measuring.



10 x

Specification

- Connectors:
2 x 8 soldering pin
- Number of positions: 8
- Pitch: 2.54 mm
- Switch position: on / off
- Switching rating: 25 mA, 24 VDC
- Insulation resistance: 100 MΩ / 500 VDC
- Withstanding voltage: 300 VAC / 1 minute
- Soldering temperature: 250 °C for ca. 3 - 5 seconds
- Environmental temperature: -40 °C ~ 85 °C
- Operating temperature: -20 °C ~ 85 °C
- Material: plastic
- Colour: blue
- Dimensions (LxWxH): ca. 21.7 x 9.9 x 5.6 mm

Item no. 66100

EAN: 4043619661008

Country of origin: China



Package: Tube



Package content

- 10 x DIP sliding switch

Images



General	
Mounting type:	Soldering
Interface	
connector:	2 x 8 soldering pin
Technical characteristics	
Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-20 °C ~ 85 °C
Resistor:	100 MΩ / 500 VDC
Physical characteristics	
Pitch distance:	2.54 mm
Material:	plastic
Length:	21.7 mm
Width:	9.9 mm
Height:	5.6 mm
Switch:	On / Off
Colour:	blue