

# Delock D-Sub25 female to Terminal Block with Enclosure

## Description

This terminal block adapter by Delock can be used to connect bare wires. Thus the adapter is not only convenient for special industry applications, but also for the hobby area, e.g. railway modelling.

### Protection by enclosure

The plastic enclosure protects the PCB from dirt and damage.

### Strain relief

The integrated strain relief fixes the cable in the enclosure.



### Item no. 66267

EAN: 4043619662678

Country of origin: Taiwan,  
Republic of China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x Parallel DB25 female with screws
  - 1 x 26 pin terminal block
- Pin assignment: 1:1
- Pitch 1 - 16 pins: 5.00 mm
- Pitch 17 - 26 pins: 3.81 mm
- Useable for a cable gauge from 26 to 18 AWG
- Operating temperature: -20 °C ~ 105 °C
- Dimensions (LxWxH): ca. 64.8 x 56.4 x 25.0 mm

## System requirements

- A free DB25 pin male

## Package content

- Adapter
- 1 x strain relief
- 2 x locking screws

## Images



## Interface

Connector 1:	1 x Parallel DB25 female with nuts
Connector 2:	1 x 26 pin terminal block

## Technical characteristics

Operating temperature:	-20 °C ~ 105 °C
------------------------	-----------------

## Physical characteristics

Pitch distance:	1 - 16 pins: 5.00 mm 17 - 26 pins: 3.81 mm
Conductor gauge:	26 - 18 AWG
Length:	64.8 mm
Width:	56.4 mm
Height:	25.0 mm