

Delock Adaptor USB 2.0 Tip-A la 1 x Serial RS-485 DB9

Descriere scurta

Acest adaptor USB 2.0 Tip-A la serie de la Delock oferă un port RS-485 pentru contoare, sisteme POS, imprimante, modemuri, dispozitive IoT etc.



Specification

- Conectori:
1 x USB 2.0 Tip-A tată >
1 x RS-485 seriale DB9 tată, cu șuruburi
- Chipset: FTDI FT232
- Rată de transfer a datelor de până la 921,6 Kbps
- Semnale: T/R (A+), T/R (B-) și GND
- Paritate: egală, impară, niciuna, marcă, spațiu
- Biți de stop: 1, 2
- Biți de date: 7, 8
- Controlul debitului: niciunul, Xon/Xoff, RTS/CTS
- FIFO: 128 Octeți - RX
- FIFO: 256 octeți - TX
- Lungime cablu, inclusiv conectori: cca 80 cm

Cerinte de sistem

- Linux Kernel 2.6 sau superior
- Mac OS 10.9 sau superior
- Windows 7/7-64/8.1/8.1-64/10/10-64/11
- PC sau laptop cu un port USB Tip-A liber

Pachetul contine

- USB 2.0 la 1 x seriale RS-485 adaptoare
- Cablu de extensie USB 2.0
- CD cu drivere
- Manual de utilizare


Nr. 66280

EAN: 4043619662807

Țara de origine: China

Pachet: Retail Box

Imagini



| General | |
|-------------------------------|--|
| Function: | Plug & Play |
| Specification: | RS-485 USB 2.0 |
| Supported operating system: | Linux Kernel 2.6 sau superior Mac OS 10.9 sau superior Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows Server 2012 R2 Windows Server 2016 |
| Interface | |
| Conector 1: | 1 x USB 2.0 Type-A male |
| Conector 2: | 1 x Serial RS-485 DB9 male |
| Technical characteristics | |
| Chipset: | FTDI 232R |
| Data transfer rate: | up to 921.6 Kbps |
| FIFO: | 128 byte 256 Byte |
| Data transmission: | asynchronous Bi-directional Semi duplex differential |
| UART: | USB to serial UART |
| Physical characteristics | |
| Cable type: | UL AWM 2725 80 °C 30V VW-1 |
| Cable colour: | black |
| Cable length incl. connector: | 80 cm |
| Pin finishing: | gold-plated |
| Shielding: | double |
| Colour: | albastru negru |