

## Delock Adapter USB 2.0 Tipa-A na 1 x serijski RS-232 DB9

### Opis

Ovaj USB 2.0 Tip-A na serijski adapter tvrtke Delock omogućava RS-232 ulaz za mjerače, POS sustave, pisače, modeme, IoT uređaje, itd.

RS-232 utikač lak za korištenje  
RS-232 spojnik odlikuje se malim dimenzijama te omogućava ugodno rukovanje na priključcima uređaja, kablskim uvodnicama, ploče za zakrpu, itd.

**1,8 m**

### Tehnički podaci

- Priključak:
  - 1 x USB 2.0 Tip-A muški >
  - 1 x serijska muška RS-232 DB9 s vijcima
- Skup čipova: FTDI FT232
- Brzina prijenosa podataka do 921,6 Kbps
- Signali: TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
- Paritet parni, neparni, nijedan, oznaka, prazno mjesto
- Stop bitova: 1, 2
- Podatkovnih bitova: 7, 8
- Kontrola protoka: nema, Xon/Xoff, RTS/CTS
- FIFO: 128 Bajta - RX
- FIFO: 256 bajta - TX
- Duljina kabela zajedno s priključkom: oko 1,8 m

### Preduvjeti sustava

- Linux Kernel 2.6 ili noviji
- Mac OS 10.9 ili noviji
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Osobno ili prijenosno računalo sa slobodnim USB Tipa-A priključkom

### Sadržaj pakiranja

- USB 2.0 na 1 x serijski adapter
- CD s upravljačkim programom
- Korisnički priručnik

### Predmet br. 66282


EAN: 4043619662821

Zemlja podrijetla: China

Pakiranje: Retail Box



### Slike



**General**

Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 2.0
Supported operating system:	Mac OS 10.9 o superiore Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Windows Server 2012 R2 Windows Server 2016 Linux Kernel 2.6 o superiore

**Interface**

Connettore 1:	1 x USB 2.0 Type-A male
Connettore 2:	1 x Serial RS-232 DB9 male

**Technical characteristics**

Chipset:	FTDI 232R
Data transfer rate:	up to 921.6 Kbps
FIFO:	128 byte 256 Byte
Data transmission:	asynchronous Bi-directional full duplex
UART:	USB to serial UART

**Physical characteristics**

Cable length incl. connector:	1,8 m
Pin finishing:	gold-plated
Shielding:	doppio
Colour:	nero