

# Delock DIP sliding switch 12-digit 2.54 mm pitch THT vertical blue 10 pieces

## Description


This DIP sliding switch by Delock is suitable for the through-hole mounting on a PCB.

## THT Assembly Technology

The attached soldering pins on the DIP switch can be inserted through contact holes on a PCB and soldered from the bottom side. The switching rows are used to set configurations and to change parameters.

## Multifunctional application

The DIP switch is mainly used in telecommunications, computers and measuring.



10 x

## Specification

- Connectors: 2 x 12 soldering pin
- Number of positions: 12
- Pitch: 2.54 mm
- Switch position: on / off
- Switching rating: 25 mA, 24 VDC
- Insulation resistance: 100 MΩ / 500 VDC
- Withstanding voltage: 300 VAC / 1 minute
- Soldering temperature: 250 °C for ca. 3 - 5 seconds
- Mechanical life: 2000 cycles
- Environmental temperature: -40 °C ~ 85 °C
- Operating temperature: -40 °C ~ 85 °C
- Material: plastic
- Colour: blue
- Dimensions (LxWxH): ca. 31.9 x 9.9 x 5.5 mm

## Item no. 66388

EAN: 4043619663880




Country of origin: China

Package: • Tube

## Package content

- 2 x DIP sliding switch

## Images



General	
Mounting type:	Soldering
Interface	
connector:	2 x 12 soldering pin
Technical characteristics	
Storage temperature:	-40 °C ~ 85 °C
Operating temperature:	-40 °C ~ 85 °C
Resistor:	100 MΩ / 500 VDC
Physical characteristics	
Pitch distance:	2.54 mm
Material:	plastic
Length:	31.9 mm
Width:	9.9 mm
Height:	5.5 mm
Switch:	On / Off
Colour:	blue