

Delock USB Type-C™ Adapter to Gigabit LAN mini

Description

The adapter by Delock expands a PC or laptop by **one network interface** via the **USB Type-CTM** interface. In addition, the adapter can also be operated on a ThunderboltTM 3 interface.

Compact design

Due to the compact dimensions the adapter is **ideal for travel**, home or office.



Item no. 66462

EAN: 4043619664627 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - 1 x USB 5 Gbps USB Type-C™ male
 - 1 x Gigabit LAN RJ45 jack
- Chipset: Realtek RTL8153B
- · Data transfer rate:

Ethernet up to 10 Mbps (Half/Full Duplex)

Fast Ethernet up to 100 Mbps (Half/Full Duplex)

Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)

USB up to 5 Gbps

- Supports IEEE 802.3 / 802.3u / 802.3ab
- Supports Auto MDI-X (automatic detection of standard or crossover network cable)
- Supports IEEE 802.3az (Energy Efficient Ethernet)
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation with back-pressure flow control
- Supports 9k Jumbo Frames
- · LED indicator for link and activity
- USB bus powered
- · Colour: black
- Metal housing





• Dimensions (LxWxH): ca. 34 x 19 x 19 mm

System requirements

- Linux Kernel 4.10 or above
- Mac OS 10.10 or above
- Windows 8.1/10/11
- Device with a free USB Type-C[™] port or with a free Thunderbolt[™] 3 port

Package content

- USB Type-C™ Gigabit LAN adapter
- User manual

Images











General

Supported operating system:	Linux Kernel 4.3 or above Mac OS 10.10 or above Windows 10 32-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows 11
LED indicator:	Link and activity

Interface

Connector 1:	1 x USB Type-C™ male
Connector 2:	1 x Gigabit LAN RJ45 jack

Technical characteristics

Chipset:	Realtek RTL8153B
Data transfer rate:	Ethernet up to 10 Mbps Fast Ethernet up to 100 Mbps Gigabit Ethernet up to 1000 Mbps

Physical characteristics

Housing colour:	black
Housing material:	Aluminium
Length:	34 mm
Width:	19 mm
Height:	19 mm