

Delock Z-Wave® Siren 100 dB

Description

This Delock siren is compatible to the Z-Wave® standard and can be connected to a Z-Wave® Gateway smoothly. Once there is a scene set, the siren sends an audible and visual signal as soon as the sensor is triggered.



Item no. 78009

EAN: 4043619780099

Country of origin: China

Package: White Box

Specification

- Z-Wave® compatible siren
- Frequency: 868.42 MHz
- Z-Wave® 500 series
- Loudness: 80 ~ 110 dB
- Power supply: battery (4 x type AAA, not included)
- 1 x inclusion / exclusion button
- Suitable for interior use
- Wall and ceiling mounting suitable
- Power consumption:
 - AOS (Always on): 365 mA
 - Static status: < 30 mA
 - Alarm status: < 220 mA
- Operating distance: ca. 30 m
- Operating temperature: 0 ~ 40 °C
- Dimension (ØxH): ca. 75 x 54 mm

System requirements

- Z-Wave® Gateway

- Z-Wave® trigger
- 4 x type AAA battery

Package content

- Z-Wave® siren
- User manual

Images



General

Mounting type:	wall Ceiling mounting
Suitable for indoor:	yes

Technical characteristics

Frequency range:	Z-Wave 868.42 MHz
Operating temperature:	0 °C ~ 40 °C
Operating range:	ca. 30 m
Voltage:	Battery (4 x type AAA, not included)

Current consumption:

Physical characteristics

Diameter:	54 mm
Length:	75 mm
Loudness:	80 ~ 110