

Delock Z-Wave® In-wall power switch

Description

This Delock LED in-wall power switch is compatible to the Z-Wave® standard and can be connected to a Z-Wave® Gateway smoothly. The in-wall power switch can be used e.g. to switch the power on or off.



Item no. 78012

EAN: 4043619780129

Country of origin: China

Package: White Box

Specification

- Z-Wave® compatible in-wall power switch
- Frequency: 868.42 MHz
- Z-Wave® 500 series
- 6 x cable connector female
- Voltage area: 220 ~ 240 V
- Max. load: 1650 W
- Max. current: 7 A / relay
- 1 x inclusion / exclusion button
- 1 x LED indicator
- Wire gauge: up to 16 AWG
- Suitable for interior use
- Power consumption: < 0.58 W (standby)
- Operating distance: ca. 30 m
- Operating temperature: 0 ~ 40 °C
- Plastic housing
- Dimension (LxWxH): ca. 52.0 x 42.0 x 15.6 mm

System requirements

- Z-Wave® Gateway

Package content

- Z-Wave® in-wall power switch
- User manual

General

Suitable for indoor:	yes
LED indicator:	1 x

Interface

connector:	6 x cable connector female
------------	----------------------------

Technical characteristics

Frequency range:	Z-Wave 868.42 MHz
Operating temperature:	0 °C ~ 40 °C
Maximum load:	1600 W
Maximum power consumption:	< 0.58 W (standby)
Maximum current:	7 A
Operating range:	ca. 30 m
Voltage area:	220 ~ 240 V

Physical characteristics

Housing material:	Plastic
Conductor gauge:	up to 16 AWG
Length:	52 mm
Width:	42 mm
Height:	15.6 mm