

Delock M12 Cable A-coded 8 pin male to RJ45 male PUR (TPU) 5 m

Description

This industrial Ethernet cable by Delock can be used to connect various components with M12 connectors, e.g. for machine control or automation.

Durable PUR (TPU) cable jacket

The material of the cable jacket makes the cable flexible and durable, making it suitable for use in drag chains and harsh environments.

The cable is oil and UV resistant and meets the high requirements for industrial applications.



5 m

Item no. 80424

EAN: 4043619804245

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x M12 male A-coded 8 pin
 - 1 x RJ45 plug
- Suitable for drag chains
- SF/UTP
- Shielding: aluminium foil, tinned copper braiding
- Copper conductor
- Cable gauge: 26 AWG
- Cable diameter: ca. 6.8 mm
- Cable jacket material: PUR (TPU)
- Max. number of bending cycles: 10,000,000
- Smallest bending radius:
 - 54.4 mm with fixed installation
 - 102.0 mm with flexible installation
- Oil-resistant
- UV-resistant
- Flammability class: UL 94
- Operating temperature:
 - 25 °C ~ 80 °C with fixed installation

-25 °C ~ 70 °C with flexible installation

- Protection class: IP67 (M12) / IP20 (RJ45)
- Colour: green
- Length incl. connectors: ca. 5 m


System requirements

- A free M12 female port
- A free RJ45 jack

Package content

- M12 cable

Images



General

Protection category:	IP67 IP20
Style:	Suitable for drag chains

Interface

Connector 1:	1 x M12 male A-coded 8 pin
Connector 2:	1 x RJ45 male

Technical characteristics

Operating temperature:	-25 °C ~ 80 °C
------------------------	----------------

Physical characteristics

Conductor material:	copper
Conductor gauge:	26 AWG
Shielding:	SF/UTP
Length:	5 m
Smallest bending radius:	54.4 mm
Colour:	green
Cable jacket material:	PUR (TPU)
Safety of Flammability:	UL 94