

# Delock M12 Cable A-coded 8 pin male to male PVC 1 m

## Description

This industrial Ethernet cable by Delock can be used to connect various components with M12 connectors, e.g. for machine control or automation.



1 m

**Item no. 80806**

EAN: 4043619808069

Country of origin: China

Package: Zip poly bag


## Technical details

- Connectors:
  - 1 x M12 male A-coded 8 pin
  - 1 x M12 male A-coded 8 pin
- Cat.5e specification
- S/FTP
- Shielding: aluminium foil, tinned copper braiding
- Copper conductor
- Cable gauge: 24 AWG (0.205 mm<sup>2</sup>)
- Cable diameter: ca. 6 mm
- Cable jacket material: PVC
- Rated current: 2 A / 30 V
- Operating temperature: -25 °C ~ 80 °C
- Protection class: IP67
- Colour: black
- Length incl. connectors: ca. 1 m

## Package content

- M12 cable

## Images



## General

Specification:	Cat. 5e
Protection category:	IP67

## Interface

Connector 1:	1 x M12 male A-coded 8 pin
Connector 2:	1 x M12 male A-coded 8 pin

## Technical characteristics

Operating temperature:	-25 °C ~ 80 °C
Maximum current:	2 A
Voltage:	30 V

## Physical characteristics

Conductor material:	copper
Conductor gauge:	24 AWG
Shielding:	S/FTP
Length:	1 m
Colour:	black
Cable diameter:	6 mm
Cable jacket material:	PVC