


Delock Cable DisplayPort 1.2 male > DVI 24+1 male passive 4K 30 Hz 5 m white

Description

This cable by Delock enables the connection between devices, e.g. a monitor, with DVI connector to a DisplayPort interface.



ca. 5 m

Item no. 83816

EAN: 4043619838165

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x DisplayPort male >
 - 1 x DVI 24+1 male with screws
- Chipset: Parade PS8402A
- DVI-D (Dual Link), VGA not wired
- DisplayPort 1.2a specification
- Passive cable (level shifter), suitable only for graphics cards with DP++ output
- Signal direction: DisplayPort input > DVI output
- Cable gauge: 30 AWG
- Cable diameter: ca. 6 mm
- Twisted-pair cabling
- Copper conductor
- Contacts gold-plated
- Triple shielded cable
- Data transfer rate up to 10.2 Gb/s
- Resolution up to 3840 x 2160 @ 30 Hz
(depending on the system and the connected hardware)
- Colour: white
- Length without connectors: ca. 5 m

System requirements

- A free DisplayPort DP++ female

Package content

- DisplayPort to DVI cable

Images



General

| | |
|----------------|------------------|
| Specification: | DisplayPort 1.2a |
|----------------|------------------|

Interface

| | |
|--------------|-------------------------------|
| Connector 1: | 1 x DisplayPort male |
| Connector 2: | 1 x DVI 24+1 male with screws |

Technical characteristics

| | |
|----------------------------|---------------------|
| Chipset: | Parade PS8402A |
| Data transfer rate: | 10.2 Gb/s |
| Maximum screen resolution: | 3840 x 2160 @ 30 Hz |

Physical characteristics

| | |
|----------------------|-------------|
| Connector finishing: | gold-plated |
| Pin finishing: | gold-plated |
| Conductor material: | copper |
| Conductor gauge: | 30 AWG |
| Shielding: | triple |
| Length: | 5 m |
| Colour: | white |