

# DisplayPort 1.2 extension cable 4K 60 Hz 7.5 m

## Description

This DisplayPort cable by Delock enables the extension of a DisplayPort connection. The triple shielded cable supports a resolution of up to Ultra HD (4K @ 60 Hz) and is downwards compatible to Full-HD 1080p.



7,5 m

## Specification

- Connectors:
  - 1 x DisplayPort 20 pin male >
  - 1 x DisplayPort 20 pin female
- DisplayPort 1.2 specification
- Pin 20 not connected
- Cable gauge: 26 AWG
- Cable diameter: ca. 8.5 mm
- Copper conductor
- Triple shielded cable
- Contacts gold-plated
- Transmission of audio and video signals
- Data transfer rate up to 21.6 Gb/s
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Colour: black
- Length incl. connectors (L): ca. 7.5 m

## Item no. 84906

EAN: 4043619849062  
Country of origin: China  
Package: Zip poly bag


## System requirements

- A free DisplayPort interface

## Package content

- DisplayPort cable

## Images



|                            |                        |
|----------------------------|------------------------|
| General                    |                        |
| Specification:             | DisplayPort 1.2        |
| Interface                  |                        |
| Connector 1:               | 1 x DisplayPort male   |
| Connector 2:               | 1 x DisplayPort female |
| Technical characteristics  |                        |
| Data transfer rate:        | 21,6 Gb/s              |
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz    |
| Physical characteristics   |                        |
| Cable diameter:            | 8.5 mm                 |
| Connector finishing:       | gold-plated            |
| Pin finishing:             | gold-plated            |
| Conductor material:        | copper                 |
| Conductor gauge:           | 26 AWG                 |
| Shielding:                 | triple                 |
| Length:                    | 7.5 m                  |
| Colour:                    | black                  |