

Delock HDMI Automotive cable HDMI-A female to HDMI-E male 3 m 4K 30 Hz

Description

This HDMI cable by Delock is used to connect a display with HDMI-E automotive connector to the multimedia system of a vehicle. Video and audio signals are transmitted.

The HDMI-E connector has a locking mechanism and has been specially developed for the requirements in the vehicle sector. It can withstand temperature fluctuations and vibrations very well and prevents the ingress of dirt or moisture.



Item no. 85287

EAN: 4043619852871 Country of origin: China Package: Zip poly bag

Specification

- Connectors:
 - 1 x HDMI-A female >
 - 1 x HDMI-E Automotive male
- High Speed Automotive HDMITM
- Cable gauge: 30 AWG
- Cable diameter: ca. 6 mm
- Copper conductor
- · Contacts gold-plated
- Connectors gold-plated
- Cable double shielded
- Data transfer rate up to 10.2 Gbps
- Resolution up to 3840 x 2160 @ 30 Hz
 (depending on the system and the connected hardware)
- Supports Dolby® TrueHD and DTS-HD Master Audio™
- · Colour: black
- Length incl. connectors: ca. 3 m



System requirements

- A free HDMI-A male port
- A free HDMI-E female

Package content

• HDMI cable

Images





General

Specification:

DTS Audio
High Speed HDMI
Dolby Digital

Interface

Connector 1: 1 x HDMI-A female

Connector 2: 1 x HDMI-E male

Technical characteristics

Data transfer rate: 10.2 Gb/s

Maximum screen resolution: 3840 x 2160 @ 30 Hz

Physical characteristics

Cable length incl. connector: 3 m

Connector finishing: gold-plated

Pin finishing: gold-plated

Conductor material: copper

Conductor gauge: 30 AWG

Shielding: double