

# HDMI Automotive cable HDMI-E male to HDMI-E male 3 m 4K 30 Hz

## Description

This HDMI cable by Delock is used to connect a display with HDMI-E automotive connector to the multimedia system of a vehicle. Video and audio signals are transmitted.

The HDMI-E connector has a locking mechanism and has been specially developed for the requirements in the vehicle sector. It can withstand temperature fluctuations and vibrations very well and prevents the ingress of dirt or moisture.



3 m

## Specification

- Connectors:
  - 1 x HDMI-E Automotive male >
  - 1 x HDMI-E Automotive male
- High Speed Automotive HDMI™
- Cable gauge: 30 AWG
- Cable diameter: ca. 6 mm
- Copper conductor
- Contacts gold-plated
- Connectors gold-plated
- Cable double shielded
- Data transfer rate up to 10.2 Gbps
- Resolution up to 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Supports Dolby® TrueHD and DTS-HD Master Audio™
- Colour: black
- Length incl. connectors: ca. 3 m

## System requirements

- Two free HDMI-E female ports

## Package content

- HDMI cable

## Item no. 85289

EAN: 4043619852895

Country of origin: China

Package: Zip poly bag

## Images



**General**

Specification:	DTS Audio High Speed HDMI Dolby Digital
----------------	---

**Interface**

Connector 1:	1 x HDMI-E male
Connector 2:	1 x HDMI-E male

**Technical characteristics**

Data transfer rate:	10.2 Gb/s
Maximum screen resolution:	3840 x 2160 @ 30 Hz

**Physical characteristics**

Cable colour:	black
Cable diameter:	6 mm
Cable length incl. connector:	3 m
Connector finishing:	gold-plated
Pin finishing:	gold-plated
Conductor material:	copper
Conductor gauge:	30 AWG
Shielding:	double