

Delock Cable DC 5.5 x 2.5 mm male to open wire ends 30 cm angled

Description

This terminal block cable by Delock can be used to connect bare wires. Thus the cable is not only convenient for special industry applications, but also for the hobby area, e.g. railway modelling. Various devices with a suitable DC power connector can be connected to the cable and are supplied with power individually (depending on the requirements of the device).



Specification

- Connectors:
 - 1 x DC 5.5 x 2.5 mm male angled >
 - 2 x open wires
- Positive pole inside, negative pole outside
- Voltage: max. 12 ~ 36 V
- Current: max. 5 A
- Cable gauge: 23 AWG
- DC pin length: ca. 9.5 mm
- Length without connectors: ca. 30 cm

Item no. 85749

EAN: 4043619857494

Country of origin: China

Package: Zip poly bag

System requirements

- A free DC female port 5.5 x 2.5 x 9.5 mm

Package content

- Cable

Images



Interface	
connector:	1 x DC 5.5 x 2.5 x 9.5 mm male
Connector 1:	2 x open wires
Technical characteristics	
Maximum current:	5 A
Voltage:	max. 12 ~ 36 V
Physical characteristics	
Conductor material:	copper
Conductor gauge:	23 AWG
Cable length without connectors:	30 cm