

# Delock PoweredUSB cable male 24 V to USB Type-A male + Mini-DIN 3 pin male 4 m for POS printers and terminals

## Description

This PoweredUSB cable by Delock can be used to connect a device with USB Type-A port and Hosiden Mini-DIN 3 pin power port to a PC or hub with PoweredUSB 24 V port. It is suitable for connecting various POS devices such as printers and terminals, e.g. by Bixolon or other manufacturers. The cable is used both for data transmission and for power supply of the connected device.



4 m

**Item no. 85943**

EAN: 4043619859436

Country of origin: China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x PoweredUSB male 24 V >
  - 1 x USB Type-A male +
  - 1 x Hosiden Mini-DIN 3 pin power male
- PoweredUSB specification
- Voltage: 24 V
- Cable gauge:
  - 26 AWG data line
  - 20 AWG power line
- Cable diameter: ca. 6.5 mm
- Cable double shielded
- Data transfer rate up to 480 Mbps
- Colour: black
- Length incl. connectors: ca. 4 m

## System requirements

- PC or hub with a free PoweredUSB 24 V female port
- Device with a free USB Type-A port and a free Hosiden Mini-DIN 3 pin power female port

---

## Package content

- PoweredUSB cable

---

## Images



## General

Specification:	PoweredUSB
----------------	------------

## Interface

Connector 1:	1 x PoweredUSB male 24 V
Connector 2:	1 x USB 2.0 Type-A male 1 x Hosiden Mini-DIN 3 pin male

## Technical characteristics

Data transfer rate:	USB 2.0 up to 480 Mb/s
Voltage:	24 V

## Physical characteristics

Cable diameter:	6.5 mm
Conductor gauge:	26 AWG data line 20 AWG power line
Shielding:	double
Length:	4 m
Colour:	black