

# Delock PoweredUSB cable male 24 V to Mini-DIN 3 pin male 2 m for POS printers and terminals

## Description

This PoweredUSB cable by Delock can be used to supply power to a device with Mini-DIN female port via a PC or hub with PoweredUSB 24 V port.



2 m

**Item no. 85946**

EAN: 4043619859467

Country of origin: China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x PoweredUSB male 24 V >
  - 1 x Hosiden Mini-DIN 3 pin power male
- PoweredUSB specification
- Voltage: 24 V
- Cable gauge: 22 AWG
- Cable diameter: ca. 5 mm
- Cable double shielded
- Colour: black
- Length incl. connectors: ca. 2 m

## System requirements

- PC or hub with a free PoweredUSB 24 V female port
- Device with a free Hosiden Mini-DIN 3 pin power female port

## Package content

- PoweredUSB cable

---

## Images



## General

Specification:	PoweredUSB
----------------	------------

## Interface

Connector 1:	1 x PoweredUSB male 24 V
Connector 2:	1 x Hosiden Mini-DIN 3 pin male

## Technical characteristics

Voltage:	24 V
----------	------

## Physical characteristics

Cable diameter:	5 mm
Conductor gauge:	22 AWG
Shielding:	double
Length:	2 m
Colour:	black