

Delock Passive DisplayPort 1.2 to HDMI Cable 4K 30 Hz 7 m

Description

This cable by Delock enables the connection between devices, e.g. a monitor, with HDMI connector to a DisplayPort interface.



Item no. 85961

EAN: 4043619859610 Country of origin: China Package: Zip poly bag

Specification

- Connectors:
 - 1 x DisplayPort male >
 - 1 x HDMI-A male
- Signal direction: DisplayPort input > HDMI output
- Chipset: Parade PS8402A
- DisplayPort 1.2 and High Speed HDMI specification
- Cable gauge: 28 AWG
- Cable diameter: ca. 7.2 mm
- · Contacts gold-plated
- Passive cable (level shifter), suitable only for graphics cards with DP++ output
- Transmission of audio and video signals
- Resolution up to 3840 x 2160 @ 30 Hz
 - (depending on the system and the connected hardware)
- Supports 3D displays (1080p @ 120 Hz)
- 2 x ferrite core
- Colour: black
- Length incl. connectors: ca. 7 m



System requirements

• A free DisplayPort female

Package content

• DisplayPort to HDMI cable

Images





General

Specification:	DisplayPort 1.2 High Speed HDMI
----------------	------------------------------------

Interface

Connector 1:	1 x DisplayPort male
Connector 2:	1 x HDMI-A male

Technical characteristics

Chipset:	Parade PS8402A
Maximum screen resolution:	3840 x 2160 @ 30 Hz

Physical characteristics

Ferrite core:	2 x
Pin finishing:	gold-plated
Conductor material:	copper
Conductor gauge:	28 AWG
Shielding:	triple
Diameter:	7.2 mm
Length:	7 m
Colour:	black