

# Delock Media Converter 10GBase-R SFP+ to 10GBase-T RJ45

#### **Description**

This 10 Gigabit Ethernet Media converter by Delock can be used to connect different media. In the SFP slot, various optional SFP+ modules up to 10 Gbps can be used.

#### **NBASE-T** for higher speed

The RJ45 port is equipped with NBASE-T for higher speeds. This allows for up to 10 Gbps data transfer rate with traditional networking cables. The best possible transfer rate is set automatically.

#### Note

This media converter can best be used for symmetrical 10 Gbps connections. For asymmetric connections (10 Gbps to 1 Gbps) we recommend the Delock media converter 86861.



#### Item no. 86439

EAN: 4043619864393 Country of origin: China Package: White Box

#### **Specification**

- · Connectors:
  - 1 x SFP slot for 10GBase-R SFP+ module
  - 1 x 10 Gigabit LAN RJ45 jack
- Data transfer rate:

Gigabit Ethernet up to 1 Gbps

NBASE-T with up to 2.5 Gbps and 5 Gbps

- 10 Gigabit Ethernet up to 10 Gbps
- · SFP module not included
- · 6 LEDs for status monitoring
- Power consumption: max. 5 W
- Operating temperature: 0 °C ~ 55 °C
- · Metal housing
- Fanless
- Dimensions (LxWxH): ca. 94 x 71 x 26 mm

# Power supply specification





• Wall power supply

• Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.4 A

• Output: 12 V / 1 A

• Ground outside, plus inside

• Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9.5 mm

## **System requirements**

• 10GBase-R SFP+ module

## **Package content**

- Media converter
- Power supply
- User manual

## **Images**









#### Interface

Output:	1 x RJ45 jack
Input:	1 x SFP jack 1 x DC 5.5 x 2.1 mm female

## **Technical characteristics**

Data transfer rate:	Gigabit Ethernet up to 1 Gbps Gigabit Ethernet up to 10 Gbps
	Gigabit Ethernet up to 2.5 Gbps Gigabit Ethernet up to 5 Gbps
Operating temperature:	0 °C ~ 55 °C

# **Physical characteristics**

Housing colour:	black
Housing material:	metal
Length:	94 mm
Width:	71 mm
Height:	26 mm

# **Power supply**

Туре:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.2 A
Output:	12.0 V / 1.0 A / 12.0 W