

# Delock Serijski kabel RS-232 D-Sub9 ženski na ženski 3 m nulti modem

## Opis

Ovaj serijski kabel tvrtke Delock je **potpuno ožičeni nulti modemska kabel** za modem, pisač, mjerne instrumente, pretvarače, RS-232 koncentratorne, patch panele, itd. Ovim kabelom dva serijska RS-232 uređaja mogu se izravno spojiti jedan na drugog radi razmjene podataka.

## Mini D-Sub9 spojnik

Ovi kabeli pristaju svakom ulazu tipa RS-232, jer su mini D-Sub9 (44 x 33,3 x 15 mm) spojnici maleni i kompaktni. Tako se RS-232 spojnici mogu koristiti odmah jedan pored drugog.

**3 m**

## Tehnički podaci

- Priključak:
  - 1 x serijska ženski D-Sub9 s vijcima >
  - 1 x serijska ženski D-Sub9 s vijcima
- Presjek kabela: 28 AWG
- Potpuno ožičeni kabel
- Dodjeljivanje pinova: 1+6 - 4, 2 - 3, 3 - 2, 4 - 1+6, 5 - 5, 7 - 8, 8 - 7, oklopljen
- Boja: crno
- Izolator: PVC
- Vrsta vijka: #4-40 UNC
- Promjer kabela: oko 5 mm
- Duljina kabela zajedno s priključkom: oko 3 m

## Preduvjeti sustava

- Slobodan D-Sub9 muški priključak.

## Sadržaj pakiranja

- Kabel


## Predmet br. 86606

EAN: 4043619866069

Zemlja podrijetla: China

Pakiranje: Plastična vrećica sa zip zatvaračem

## Slike





| General                       |  |
|-------------------------------|--|
| Tehnički podaci:              | RS-232 (EIA / TIA)                     |
| Style:                        | Null Modem<br>Mini Sub-D9              |
| Interface                     |  |
| Priključak 1:                 | 1 x serijska ženski D-Sub 9 s vijcima  |
| Priključak 2:                 | 1 x serial Sub-D 9 female with screws  |
| Technical characteristics     |  |
| Brzina prijenosa podataka:    | up to 921.6 Kbps                       |
| Signal transmission:          | TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND |
| Physical characteristics      |  |
| Cable type:                   | AWM Style 2464 28 AWG 80 °C 300 V VW-1 |
| Promjer kabela:               | 5 mm                                   |
| Cable length incl. connector: | 3 m                                    |
| Površinska zaštita kontakata: | pozlaćeni                              |
| Conductor material:           | Copper tinned                          |
| Conductor gauge:              | AWG 28                                 |
| Vrsta vijka:                  | #4-40 UNC                              |
| Boja:                         | crni                                   |
| Cable jacket material:        | PVC                                    |
| Safety of Flammability:       | VW-1                                   |