

Delock Serial Cable RS-232 Sub-D9 female to female null modem with narrow plug housing 1 m

Description

This serial cable by Delock is a **full handshaking null modem cable** for printers, measuring instruments, converters, RS-232 hubs, patch panels etc. With this cable, two serial RS-232 devices can be connected to each other for data exchange.

Mini Sub-D9 connector

These cables fit any RS-232 port, as the **mini Sub-D9 connectors** (44 x 33.3 x 15 mm) are small and compact. In this way, RS-232 connections can be used directly adjacent to each other.



1 m

Specification

- Connectors:
 - 1 x serial Sub-D9 female with screws >
 - 1 x serial Sub-D9 female with screws
- Cable gauge: 28 AWG
- Full handshaking cable
- Pin assignment: 1+6 - 4, 2 - 3, 3 - 2, 4 - 1+6, 5 - 5, 7 - 8, 8 - 7, shielded
- Colour: black
- Insulator: PVC
- Screw type: #4-40 UNC
- Cable diameter: ca. 5 mm
- Cable length incl. connectors: ca. 1 m

System requirements

- A free Sub-D9 male port

Package content

- Cable

Item no. 86608

EAN: 4043619866083

Country of origin: China

Package: • Zip poly bag

Images



General	
Specification:	RS-232 (EIA / TIA)
Style:	Null Modem Mini Sub-D9
Interface	
Connector 1:	1 x serial Sub-D 9 female with screws
Connector 2:	1 x serial Sub-D 9 female with screws
Technical characteristics	
Data transfer rate:	up to 921.6 Kbps
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND
Physical characteristics	
Cable type:	AWM Style 2464 28 AWG 80 °C 300 V VW-1
Cable diameter:	5 mm
Cable length incl. connector:	1 m
Pin finishing:	gold-plated
Conductor material:	Copper tinned
Conductor gauge:	28 AWG
Screw type:	#4-40 UNC
Shielding:	Aluminum foil
Colour:	black
Cable jacket material:	PVC
Safety of Flammability:	VW-1