

Delock DisplayPort 1.2 cable female to female panel-mount 4K 60 Hz 1 m

Description

This cable by Delock can be used to extend a DisplayPort connection and to connect various devices. The female port can be attached with two screws, e.g. to a slot bracket, a cable duct or an enclosure with the corresponding opening. In this way, it is possible to install a DisplayPort connector in an easily accessible position.



Item no. 87100

EAN: 4043619871001

Country of origin: China

Package: Box

Specification

- Connectors:
 - 1 x DisplayPort female >
 - 1 x DisplayPort female panel-mount
- DisplayPort 1.2 specification
- Pin 20 is connected (supports 3.3 V)
- Screw type: M3
- Screw distance: 27 mm
- Cable gauge: 28 AWG
- Cable diameter: ca. 7 mm
- Copper conductor
- Triple shielded cable
- Contacts gold-plated
- Transmission of audio and video signals
- Data transfer rate up to 21.6 Gbps
- Resolution up to 3840 x 2160 @ 60 Hz
(depending on the system and the connected hardware)
- Supports HDR
- Supports HDCP 1.4 and 2.2
- Colour: black

- Length incl. connectors: ca. 1 m

System requirements

- A free DisplayPort interface

Package content

- DisplayPort panel-mount cable
- 2 x screw

Images



General

| | |
|----------------|--|
| Specification: | DisplayPort 1.2 HDCP 1.4 HDCP 2.2 HDR |
|----------------|--|

Interface

| | |
|--------------|------------------------|
| Connector 1: | 1 x DisplayPort male |
| Connector 2: | 1 x DisplayPort female |

Technical characteristics

| | |
|----------------------------|---------------------|
| Data transfer rate: | 21,6 Gb/s |
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz |

Physical characteristics

| | |
|---------------------|-------------|
| Pin finishing: | gold-plated |
| Conductor material: | copper |
| Conductor gauge: | 28 AWG |
| Screw distance: | 27 mm |
| Screw type: | M3 |
| Shielding: | triple |
| Length: | 1 m |
| Colour: | black |