

Delock Gigabit Ethernet Switch 4 Port PoE + 1 RJ45 + 1 SFP

Description

This Gigabit Ethernet Switch by Delock can be used to connect different network components. The four RJ45 ports support Power over Ethernet according to IEEE802.3af / 802.3at, so they can supply power to PoE-enabled devices, such as an IP camera or a PoE splitter via the network cable. In addition, a fifth RJ45 uplink port is available without PoE function. The built-in SFP slot allows to expand the network with a fiber optic connection.



Item no. 87702

EAN: 4043619877027

Country of origin: Taiwan,
Republic of China

Package: White Box

Specification

- Connector:
 - 4 x RJ45 jack for 10/100/1000 Mb/s Base-T (PoE+)
 - 1 x RJ45 jack for 10/100/1000 Mb/s Ethernet (Uplink)
 - 1 x SFP slot for 1 Gb/s SFP module (SFP module not included)
 - 1 x DC jack 5.5 x 2.1 mm (power)
- Data transfer rate up to 1 Gb/s
- LEDs for status monitoring: Power, Link / Activity, PoE
- Supports IEEE802.3at (PoE+) and 802.3af (PoE)
- Phantom power (Mode A, pairs 1/2 and 3/6)
- Power supply: max. 30 W per PoE port, max. 60 W total
- Power consumption: max. 72 W
- Metal housing
- Fanless
- Dimensions (LxWxH): ca. 141 x 94 x 26 mm

Power supply specification

- Power supply with IEC connector
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2.0 A
- Output: DC 52 V / 1.38 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9 mm

System requirements

- Device with one free RJ45 port

Package content

- PoE switch
- External power supply
- Power cord
- User manual

Images



Interface

Output:	4 x RJ45 female (PoE)
Input:	1 x 5 V DC female 5,5 mm x 2,1 mm 1 x RJ45 jack 1 x SFP jack

Technical characteristics

Data transfer rate:	Gigabit Ethernet up to 1 Gbps
---------------------	-------------------------------

Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	141 mm
Width:	94 mm
Height:	26 mm

Power supply

Type:	Power supply with IEC connector
Input:	AC 100 - 240 V / 50 - 60 Hz / 2.0 A
Output:	52 V / 1.38 A
Connector:	DC male 5.5 mm x 2.1 mm