

Delock DisplayPort 1.2 Splitter 1 x DisplayPort in > 2 x HDMI out 4K 30 Hz

Description

This splitter by Delock is suitable for the connection of two HDMI monitors to a computer with DisplayPort interface. Two monitors can be operated simultaneously at the outputs.

Note

The product is a Multi-Stream-Transport (MST) hub and supports the extended desktop configuration of Displayport 1.2. When Mac OS is used, the same image is displayed on both ports (mirrored), it is not possible to use both ports independently of each other.



Item no. 87720

EAN: 4043619877201

Country of origin: China

Package: Retail Box

Specification

- Connectors:
Input:
1 x DisplayPort 20 pin male
1 x USB Type Micro-B female (5 V power supply)
Output:
2 x HDMI-A 19 pin female
- Chipset: STDP4320
- DisplayPort 1.2 specification
- Resolution up to 2560 x 1440 @ 60 Hz / 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Functions: Mirrored or Extended (Windows only)
- Transfer of audio and video signals
- Colour: black
- Cable length incl. connectors: ca. 25 cm
- Dimensions (LxWxH): ca. 61 x 49 x 11 mm

System requirements

- Windows 8.1/8.1-64/10/10-64, Mac ex OS 10.9
- One free DisplayPort female
- Charger 1 x USB Type-A 5 V / 1 A

Package content

- DisplayPort Splitter
- USB power cable, length: ca. 0.5 m
- User manual

Images



General

Specification:	DisplayPort 1.2
Supported operating system:	Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

Output:	2 x HDMI-A female
Input:	1 x DisplayPort male 1 x USB Type Micro-B female (5 V power supply)

Technical characteristics

Chipset:	STDP4320
Maximum screen resolution:	3840 x 2160 @ 30 Hz

Physical characteristics

Housing colour:	black
Housing material:	Plastic
Cable length incl. connector:	25 cm
Length:	61 mm
Width:	49 mm
Height:	11 mm