

Delock Multi-AV to HDMI Converter 4K 60 Hz

Description

This multi-functional converter by Delock makes it possible to convert different sources into one HDMI signal. The signal inputs are USB-CTM (DP Alt Mode), VGA with 3.5 mm audio, Mini DisplayPort and HDMI. The converter box is a practical solution for connecting various audio / video devices to a projector or TV with HDMI input.



Item no. 87732

EAN: 4043619877324 Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

• Connectors:

Input:

- 1 x mini DisplayPort 20 pin female
- 1 x HDMI-A 19 pin female
- 1 x USB Type-CTM (DP Alt Mode) female
- 1 x VGA 15 pin female with nuts
- 1 x 3.5 mm 3 pin stereo jack female
- 1 x DC 5 V power connector
- 1 x RJ45 jack

Output:

- 1 x HDMI-A 19 pin female
- 1 x RJ45 jack
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Resolution (VGA input) up to 1920 x 1080 @ 60 Hz
- Transmission of audio and video signals
- Switching automatic or via button
- · Robust metal housing
- Dimensions (LxWxH): ca. 179 x 80 x 25 mm





Power supply specification

· Wall power supply

• Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.5 A

• Output: 5 V / 2.5 A

• Ground outside, plus inside

• Dimensions:


inside: ø ca. 2.5 mm outside: ø ca. 5.5 mm length: ca. 9.5 mm

Package content

- Converter
- · Mounting bracket
- Power supply
- User manual

Images













Interface

| Output: | 1 x RJ45 jack 1 x HDMI-A female |
|---------|---|
| Input: | 1 x HDMI-A female 1 x mini DisplayPort 20 pin female 1 x 3.5 mm 3 pin stereo jack female 1 x RJ45 jack 1 x USB Type-C™ female 1 x VGA 15 pin female 1 x DC female |

Technical characteristics

|--|

Physical characteristics

| Length: | 179 mm |
|---------|--------|
| Width: | 80 mm |
| Height: | 25 mm |