

Delock Thunderbolt™ 3 Docking Station 8K - Dual DisplayPort / USB / LAN / SD / Audio / PD 3.0

Description

This Thunderbolt™ 3 docking station by Delock can be connected to a computer with a Thunderbolt™ 3 port and provides a variety of interfaces. Up to **two monitors can be operated simultaneously** at the DisplayPort outputs. **Four built-in USB ports** allow the use of peripherals, connections for **headset** and **Gigabit network**, as well as **SD and Micro SD slot** complete the features.



Certified

Multi-Stream Transport (MST)

The product is an MST hub and supports the extended desktop configuration of DisplayPort. This allows multiple monitors to be combined into one large display. The maximum resolution for simultaneous playback on two or three monitors depends on the system and connected hardware.

USB Power Delivery (USB PD 3.0) support up to 60 watt

The docking station has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it.

Note

Only one additional external monitor can be connected to MacBook devices with M1 chipset.

Specification

- Connectors:
 - 1 x Thunderbolt™ 3 female >
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) USB Type-C™ female
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female - Battery Charging specification BC1.2
 - 1 x SuperSpeed USB 10 Gbps (USB 3.2 Gen 2) Type-A female



Item no. 87777

EAN: 4043619877775

Country of origin: China

Package: Retail Box

- 1 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
- 2 x DisplayPort female
- 1 x Gigabit LAN 10/100/1000 Mbps RJ45 jack
- 1 x Headset 3.5 mm 4 pin jack
- 1 x SD slot
- 1 x Micro SD slot
- 1 x DC jack
- Chipset: Intel Titan Ridge
- Maximum resolution (depending on the system and the connected hardware):
with DSC:

Single Display	7680 x 4320 @ 30 Hz
Dual Display SST	3840 x 2160 @ 60 Hz + 3840 x 2160 @ 60 Hz
Dual Display MST	7680 x 4320 @ 30 Hz + 3840 x 2160 @ 60 Hz

without DSC:

Single Display	3840 x 2160 @ 60 Hz
Dual Display SST	3840 x 2160 @ 60 Hz + 3840 x 2160 @ 60 Hz
Dual Display MST	3840 x 2160 @ 60 Hz + 3840 x 2160 @ 60 Hz

- Transmission of audio and video signals
- Functions: Mirrored or Extended
- Supports HDCP 2.2
- Supports HDR
- Headset jack: auto detection OMTP or CTIA standard
- SD / Micro SD slot: supports SD 3.0 (UHS-I), SD 4.0 (UHS-II)
- Plug & Play
- Output power for host: max. 60 W
- Colour: grey
- Dimensions (LxWxH): ca. 147 x 80 x 17 mm

Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 3.0 A
- Output: 20 V / 6 A
- Ground outside, plus inside
- Dimensions:
inside: ø ca. 3.0 mm
outside: ø ca. 4.5 mm
length: ca. 10 mm

System requirements

- Mac OS 10.15.3 or above
- Windows 8.1/8.1-64/10/10-64
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- Thunderbolt™ 3 docking station
- Thunderbolt™ 3 cable, length ca. 50 cm
- Power supply
- User manual

Images



Maximum resolution (depending on the system and the connected hardware)

with DDC:	
Single Display	7680 x 4320 @ 60 Hz
Dual Display DSD	5940 x 2160 @ 60 Hz + 5940 x 2160 @ 60 Hz
Dual Display DSDT	7680 x 4320 @ 60 Hz + 5940 x 2160 @ 60 Hz
without DDC:	
Single Display	3840 x 2160 @ 60 Hz
Dual Display DSD	5940 x 2160 @ 60 Hz + 5940 x 2160 @ 60 Hz
Dual Display DSDT	5940 x 2160 @ 60 Hz + 5940 x 2160 @ 60 Hz

General

Function:	HDR / HDR10
Supported operating system:	Mac OS 10.15.3 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Technical characteristics

Maximum screen resolution:	7680 x 4320 @ 30 Hz
----------------------------	---------------------

Physical characteristics

Housing material:	metal
Length:	147 mm
Width:	80 mm
Height:	17 mm
Colour:	grey