


Delock HDMI Automotive cable HDMI-A female to HDMI-E male 3 m 4K 60 Hz

Description

This HDMI cable by Delock is used to connect a display with HDMI-E automotive connector to the multimedia system of a vehicle. Video and audio signals are transmitted.

The HDMI-E connector has a locking mechanism and has been specially developed for the requirements in the vehicle sector. It can withstand temperature fluctuations and vibrations very well and prevents the ingress of dirt or moisture.



3 m

Item no. 87905

EAN: 4043619879052

Country of origin: China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x HDMI-A female >
 - 1 x HDMI-E Automotive male
- High Speed Automotive HDMI™
- Cable gauge: 30 AWG
- Cable diameter: ca. 6 mm
- Copper conductor
- Contacts gold-plated
- Connectors gold-plated
- Cable double shielded
- Data transfer rate up to 18 Gbps
- Resolution up to 3840 x 2160 @ 60 Hz
(depending on the system and the connected hardware)
- Supports Dolby® TrueHD and DTS-HD Master Audio™
- Colour: black
- Length incl. connectors: ca. 3 m

System requirements

- A free HDMI-A male port
 - A free HDMI-E female
-

Package content

- HDMI cable
-

Images



General

| | |
|----------------|-----------------------------------------------|
| Specification: | DTS Audio High Speed HDMI Dolby Digital |
|----------------|-----------------------------------------------|

Interface

| | |
|--------------|-------------------|
| Connector 1: | 1 x HDMI-A female |
| Connector 2: | 1 x HDMI-E male |

Technical characteristics

| | |
|----------------------------|---------------------|
| Data transfer rate: | 10.2 Gb/s |
| Maximum screen resolution: | 3840 x 2160 @ 60 Hz |

Physical characteristics

| | |
|-------------------------------|-------------|
| Cable colour: | black |
| Cable length incl. connector: | 3 m |
| Connector finishing: | gold-plated |
| Pin finishing: | gold-plated |
| Conductor material: | copper |
| Conductor gauge: | 30 AWG |
| Shielding: | double |