
Delock PCI Express Karte > Hybrid 1 x intern SATA 6 Gb/s + 1 x intern mSATA

Description

The PCI Express card by Delock expands your PC by one SATA 6 Gb/s port and one mSATA port. The card offers a hyperduo function. With this function you can combine a mSATA module and a HDD to use the advantages of both data mediums. The speed of a SSD and the capacity of a HDD. The card also supports the common NON-RAID, RAID0 and RAID1 functions.



Item no. 89302

EAN: 4043619893027

Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

- Connector:
  1 x internal SATA 6 Gb/s
  1 x internal mSATA (mini PCIe, full size)
- Supports RAID0, RAID1, HyperDuo Virtual Disk (Save/Capacity) and NON-RAID
- Hyperduo function, Safe Mode, Capacity Mode
- Supports HDD and SSD drives
- Supports Native Command Queuing (NCQ)
- Supports ATA, ATAPI
- Supports Port Multiplier FSI or Switching
- PCI Express x1, V2.0
- Compatible to PCIe 1.0 and 2.0
- Form factor low profile
- Temperature range:
  operating: + 5° C to + 50° C
  nonoperating: - 25° C to + 70° C
- Humidity:
  operating: 20 % to 80 %

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

nonoperating: 15 % to 90 %
- Power consumption: ca. 1 W

System requirements


- Windows XP/XP-64/Vista/Vista-64/7/7-64/8/8.1
- PC with one free PCI Express slot


Package content

- PCI Express card
- Low profile bracket
- Driver CD
- User manual

Images








© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.