

Delock WLAN Antenna 802.11 ac/a/b/g/n SMA 4 - 5 dBi omnidirectional joint black

Description

This WLAN antenna is designed to connect to devices with SMA interface, in order to send and receive WLAN dual band signals.



Item no. 89438

EAN: 4043619894383

Country of origin: Taiwan,
Republic of China

Package: Zip poly bag

Specification

- Connector: SMA plug
- With flexible joint, rotatable
- Frequency range:
 - 2.4000 ~ 2.4835 GHz
 - 5.1500 ~ 5.7250 GHz
- Impedance: 50 Ohm
- Antenna gain: 4 -5 dBi
- VSWR: 2.0 max.
- Operating temperature: -20 °C ~ 65 °C
- Length:
 - with flexible joint: ca.195 mm
 - without flexible joint: ca.165 mm
- Diameter:
 - peak: ca. 6.0 mm
 - SMA: ca. 12.5 mm





System requirements

- Device with SMA connector

Package content

- WLAN antenna SMA

Images



General

Suitable for indoor:	yes
----------------------	-----

Interface

connector:	SMA Stecker
------------	-------------

Technical characteristics

Frequency range:	2.4000 GHz - 2.4835 GHz 5.1500 - 5.7250 GHz
Antenna gain:	4 - 5 dBi
Beam width horizontal:	360°
Impedance:	50 Ω
Operating temperature:	-20 °C ~ 65 °C
Polarisation:	linear vertical
VSWR:	2.0

Physical characteristics

Housing colour:	black
Housing material:	TPEE
Diameter:	12.5 cm
Length:	19.6 cm